# Product data sheet


SRT-SYSTEM IP64-SRGSVCTB PP/1500 LED - GERÄTETRÄGER VARIABEL CENTRAL.LINE.OPTIC | DEVICE MOUNT VARIAB.. 9000 865 IP64 DALI2 SW RAL 9005 (SRT+19537006174)

REGIOLUX



SRT-Quick-fit mounting system, IP 64 variable device mount, Modullänge/1500. Device mounts made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantees good corrosion protection; tool-free attachment with design-integrated push locks ensure protection against theft and disassembly. Integrated end faces made of plastic with sealing lips and an all-round closed seal to the support rail for a protection type up to IP64. Variable position on the support rail. Housing colour black RAL 9005. Performance level: Powerful Performance (PP) - Powerful, universal all-rounder, sets very high standards for efficiency, service life and warranty period, Light distribution direct narrow/wide distribution by means of Central.Line.Optic of PMMA plastic, The lens optics ensure ease of installation and are easy to maintain thanks to the easy-to-clean surface. The density of the single-row lens arrangement ensures that the points merge into a line with a homogeneous appearance in the object. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a 1m connection cable for variable device mount positioning with a 5-pin, quick-fit plug connector in the light run with free phase pre-selection. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Dimensions (LxWxH): 1535mm x 55mm x 37mm Beam angle: 80°(C0)/80° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 6500K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG1 LED service life: 75000h L80/B10 (Tq 40°C), 100000h L80/B50 (Tq 40°C) Nominal luminous flux: 8378lm Luminaire luminous efficiency: 171lm/W Control gear: Electronic driver DALI2 (1 pcs.) System output: 49W Energy efficiency class/light source: B Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (-20°C bis 40°C) Ambient temperatur: ta -20°C to 40°C Special properties: Ready for IoT UGR lat./long.: max. 20.5 / 19.5 Certification mark: IP64, Protection class I, ENEC10 VDE, F, D, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 7 years Regiolux GmbH Type: SRGSVCTB PP /1500 LED 9000 865 DALI2 sw RAL 9005 Article number: 19537006174 Product deep link: https://www.regiolux.de/en/article/19537006174 General warranty conditions: www.regiolux.de/en/Service/Warranty

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | | CCT | 6500 K |
| Nominal lamp power | 49.1 W | CRI | 80 |
| Total flux | 8378 lm | LOR | 100% |
| Luminous efficacy | 171 lm/W | Total power | 49.1 W |

### Mounting mode

Ceiling mounted, Contact rail

### Shape and measurements

Length: 60.43 in

Width: 2.48 in

Height: 2.64 in

### Electric

System power: 49.1 W

Appliance Class: 0

## Design

Color of housing: Black

## Protection

IP: 64

IK: 03

Designation labels: CE, ENEC