Product data sheet

BRISA-FRB-PA08-48LED-3000K-4860LM-29.1W


LIGHTRONICS



IP 66 IK 10

BRISA FUNCTIONALLY COMPLETE From residential streets to access roads: the BRISA makes it possible to illuminate the entire living environment with a single luminaire line. The BRISA has specific variants for crossings, cycle paths and for protecting flora and fauna. This versatility makes the BRISA line suitable for business parks, industrial estates, ecological zones, parking spaces, large car parks, cycle paths, roundabouts, holiday parks, footpaths and residential areas. All the luminaires in the BRISA line are impact-resistant (IK 10) and waterproof (IP 66).

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	29.1 W	CRI	70
Total flux	78 lm	LOR	100%
Luminous efficacy	3 lm/W	ULOR	2%
		Total power	29.1 W

Mounting mode

Pole integrated, Pole top mounted

Shape and measurements

Length: 21.54 in
Width: 9.84 in
Height: 3.94 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: Black, Anthracite / graphite, Silver gray

Electric

System power: 29.1 W

Protection

IP: 66
IK: 10