


Product data sheet

FREESTANDING LUMINAIRE TWEAK OFFICE TWIN HEAD 84W CRI > 80
2004.6967 - TWEAK2 S2U1950 LED12200-840 SR 01FSEDI EU
REGENT




Freestanding luminaire Tweak Office twin head, with LED, system power: 84 W, standby power 1 W, luminous flux of luminaire 12200 lm, colour rendering index CRI > 80, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 ($UGR < 19$; $L_{max} \geq 65^\circ \leq 3000 \text{ cd/m}^2$), photobiological safety: the luminaire poses no danger (RG0), 230 V, direct-indirect light emission, 27%/73%, common dimmable and switchable, without control element, luminaire head 2x90°adjustable, one-piece housing in die-cast aluminium, silver, VAG E 1, thermo painted, office-suitable microprismatic CLD optics (Controlled Luminance Diffusor) for perfect glare control, 2 integral control gears, SensoDim®, with light/movement sensor, base plate, U-shaped, 3m power supply cable with IEC 7/7 european plug, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0309), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP20, glow wire test 650 °C, this product contains a light source of energy efficiency class C and EPREL registration number: 1140598 L = 651 mm, B = 535 mm, total height = 1950 mm

Light output 1



1 x LED			
Nominal lamp power	42 W	LOR	100%
Lamp flux	6100 lm	ULOR	82%
Luminous efficacy	145 lm/W	Total flux	6099 lm
CCT	4000 K	Total power	42 W
CRI	80		

Light output 2



1 x LED			
Nominal lamp power	42 W	LOR	100%
Lamp flux	6100 lm	ULOR	82%
Luminous efficacy	145 lm/W	Total flux	6099 lm
CCT	4000 K	Total power	42 W
CRI	80		

Mounting mode

Standing / Bollard

Electric

System power: 84 W

Appliance Class: I

Shape and measurements

Length: 25.59 in
Width: 21.06 in
Height: 76.77 in
Weight: 21.972 kg

Adjustability

Free

Design

Color of housing: Silver gray

Protection

IP: 20