

Product data sheet


MRZ-4 MULTI-HEAD RECESSED INTEGRAL LED
MRZ-1-REC-X-3-L27-80-FL-UNV-X-STD-SFL
COOPER LIGHTING



IP
47

Family of 1, 2, 3, or 4-head fixtures, Lumen packages from 250 to 1700+ per head in 80+ or 97+ CRI, +110 LPW, 25°, 40°, 55° optics; each head has 45° tilt with 365° degree rotation, Black housing & white trim/white housing & trim/black housing & trim, IC-rated fixtures with flanged and mud-in trims, 0-10V std dimming. Optional: 0.1%, 1%, Lutron, and Fifth Light DALI, LumaWatt Pro and WaveLinx connected lighting platforms available, Linear spread lens, soft focus lens, hex louver, and snoot option, Chicago plenum and emergency battery options

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 2700 K |
| Nominal lamp power | 12.1 W | CRI | 80 |
| Total flux | 1166 lm | LOR | 100% |
| Luminous efficacy | 96 lm/W | Total power | 12.1 W |

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.39 in
Diameter: 2.00 in

Adjustability

Fixed

Electric

System power: 12.1 W

Protection

IP: 47