


Product data sheet

SLOIN A SL BWS LED5200-840 L3024 PC
42185040
ZUMTOBEL



LED light line with DALI-controllable LED converter, with cover to 50m from one piece; LED service life lasts 50000 h before luminous flux is reduced to 90% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 4960 lm, Luminaire efficacy: 105 lm/W. Colour rendering Ra > 80, colour temperature 4000 K. Luminaire of aluminium, silver powder coated. Luminaire with completely uniform appearance due to polycarbonate cover. Luminaire consists of housing and continuous optic of polycarbonate. Includes gear tray, wiring, and end-cap set. Luminaire wired with halogen-free leads and covers are due to norm classified as TP(a). Degree of protection: IP40 below (IP20 above). Dimensions: 3024 x 76 x 98 mm weight: 12.5 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	47.2 W	CRI	80
Total flux	4960 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	47.2 W

Mounting mode

Pendant

Shape and measurements

Length: 119.06 in
Width: 2.99 in
Height: 3.86 in
Weight: 12.5 kg

Design

Material impression: Aluminum
Color of housing: Silver gray

Electric

System power: 47.2 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: I

Protection

IP: 20
IK: 07
Designation labels: CE, ENEC