Product data sheet


TRIONA RECTANGLE A
312707.004.76
RZB



IP 20 IK 03

Series: TRIONA rectangle Decorative rectangular LED surface-mounted luminaire. Flat, seamless frame: aluminium extrusion profile, powder coated. Cover made of sheet steel, powder-coated. Diffuser made of non-yellowing plastic (PMMA) microprismatic. LED backlight technology for homogeneous illumination of the entire light-emitting surface. Suitable for Ceiling mounting, Wall (surface). Very easy installation thanks to plug-and-play connector system. Integrated DALI converter for controlling, switching and dimming. Suitable for through-wiring. Colour: silver, matt (approx. RAL 9006) Length: 1040 mm Width: 350 mm Height: 88 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 30 W Rated luminous flux: 3950 lm Beam angle Down: 93° / 95° Luminous efficiency: 132 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	30 W	CRI	80
Total flux	3950 lm	LOR	67%
Luminous efficacy	132 lm/W	ULOR	14%
		Total power	30 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 13.78 in
Width: 40.94 in
Height: 3.46 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 30 W

Protection

IP: 20
IK: 03