

# Product data sheet

KP\_242\_P3M\_LED\_25W\_NEUTRAL\_L600MM


622583

PETRIDIS



Technical Features - Luminaires for LED CHIP. - Recessed luminaires for armstrong ceiling. - Steel body, electrostatically painted in white colour. - Aluminium louvre with high efficient satin PMMA cover for louvre version. - Pure light without IR/UV radiation. - Efficient thermal management. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10). - Conection for operation on 230V/50-60Hz. Upon request: - Available with highest colour rendering index (CRI). - Connection for emergency lighting system, for one or three hours

## Light output 1



1 x LED			
Nominal lamp power	25 W	LOR	76%
Lamp flux	4220 lm	Total flux	3190 lm
Luminous efficacy	169 lm/W	Total power	25 W
CCT	4000 K		
CRI	80		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 23.62 in

Width: 8.39 in

Height: 3.54 in

## Adjustability

Fixed

## Design

Material impression: Aluminum, Gloss, Plastic

## Electric

System power: 25 W

Controller: Dimmable 1..10V, DALI

Appliance Class: I

## Protection

IP: 20

Designation labels: CE