


Product data sheet

PLAY IP65 ROUND FIXED EMERGENCY
AG16-13X9M2O360
LEDSC4




LedsC4 Play IP65 Round Fixed Emergency AG16-13X9M2O360 Downlight For downlighting. Structure material: Aluminium. Structure finish: Black. Diffuser material: Glass. Diffuser finish: Transparent. Warranty: 5 Years. Product net weight (Kg): 0.83 Product width or diameter (mm): 93 Product height (mm): 101 Ø of the hole for recessing (mm): 65 Permitted ceiling thickness: 0-20 Class 2. Luminaire not suitable for coating with insulation materials. Glow wire test: 850. IP: IP65. IK: IK03. LED. No. of lampholders or LEDs: 1. LED brand: CREE. Driver brand: VOSSLOH-SCHWABE. Maximum power of light source: 11.9W. Colour temperature: 4000K. Colour rendering index: 90. MacAdam Steps: 2. Hours of life: 50.000h L80B20. UGR: 17.8. Photobiological risk: RG2. % de Flickering: <5%. Real flux (lm): 1242. Real lm/W: 87. Voltage / frequency range: 100-240/50-60Hz. Voltage: 36. Equipment included: Yes. Total power: 14.3. Power factor: 0.88. Dimmable equipment included: ON-OFF. Emergency supply provision.

Light output 1 (emergency)



1 x LED			
Nominal lamp power	1.9 W	LOR	100%
Lamp flux	165 lm	Total flux	165 lm
Luminous efficacy	87 lm/W	Total power	1.9 W
CCT	4000 K		
CRI	90		



1 x LED			
Nominal lamp power	14.3 W	LOR	100%
Lamp flux	1242 lm	Total flux	1241 lm
Luminous efficacy	87 lm/W	Total power	14.3 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.66 in
Width: 3.66 in
Height: 0.08 in

Electric

System power: 1.9-14.3 W
Appliance Class: II

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 65

IK: 03