


Product data sheet

MAXIFRANCO
971914
FLOS



Outdoor luminaire for installation on wall or on pole. Configuration: die-cast aluminium structure. EN AB-47100 (low copper content) Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Pure aluminium optics, tempered extra-clear glass diffuser, silicone gaskets. The luminaire is equipped with a graduated stainless steel fixing plate allowing a precise installation on the wall.

Light output 1



1 x Metal halide lamp			
Nominal lamp power	150 W	Socket	Rx7S
Lamp flux	11250 lm	LOR	59%
Luminous efficacy	44 lm/W	Total flux	6591 lm
CCT	4200 K	Total power	150 W
CRI	98		

Mounting mode

Wall mounted

Shape and measurements

Length: 11.42 in

Width: 5.91 in

Height: 15.75 in

Adjustability

Tiltable

Electric

System power: 150 W

Appliance Class: I

Protection

IP: 65

IK: 07