


Product data sheet

PH 6½-6 LED 2700K 96W
5741094943
LOUIS POULSEN



PH 5-4½ & PH 6½-6 Design : Poul Henningsen Concept : The trumpet-shaped top shade on the fixture provides illumination of the area above the three shades, which primarily direct the light downwards. A base reflector and a blue glare ring protect against glare from all angles. The strongest light is directly under the fixture. The shades have a matte white painted finish to ensure very comfortable lighting. Finish : White. Material : Shades: Spun aluminium. Anti-glare disc: Blue, spun aluminium. Struts: Rolled aluminium coloured. Mounting : Suspension type: Cable 3x0,75mm² or cable 3x0,75mm² & wire. Canopy: Yes. Cable length: PH 5-4½: 3m, PH 6½-6: 4m. Class : Ingress protection IP20. Electric shock protection I w. ground. Weight : Max. 6kg.

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	96 W	CRI	90
Total flux	4684 lm	LOR	100%
Luminous efficacy	49 lm/W	ULOR	10%
		Total power	96 W

Mounting mode

Pendant

Shape and measurements

Height: 12.52 in

Diameter: 18.35 in

Adjustability

Fixed

Electric

System power: 96 W

Appliance Class: I

Protection

IP: 20