



Product data sheet

840 LED PANEL - UGR<LT/>19 - CRI<GT/>90 4000K CRI 90 47W CLD WHITE
150211-00
DISANO



Housing: body in steel sheet and frame in aluminium. Diffuser: in high transmittance prismatic technopolymer. Internal PMMA slab. : Art 150211-00: not UGR<lt/>19 Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: Ceiling lighting fixture with external driver; it can be easily housed in false ceilings. Mounting: surface mounting on T-beams. Easy installation: quick connection without the need to open the luminaire, can be easily inserted into the ceiling. On request: - DIMM DALI CLD-D wiring (subcode -0041) - CLD-D (PUSH) (subcode -0045)

Light output 1



1 x LED			
Nominal lamp power	47 W	LOR	100%
Lamp flux	4250 lm	Total flux	4250 lm
Luminous efficacy	90 lm/W	Total power	47 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.46 in
Width: 23.46 in
Height: 0.47 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 47 W
Appliance Class: II

Protection

IP: 43
IK: 06
Designation labels: CE, ENEC