

Product data sheet


SHADOW LIGHTS STAGE 2 INSERT KEY 4000K
26.30600.0V001 + 26.41000.0V00X
HESS



IP
65


INSERT SHADOW LIGHTS STAGE 2 INSERT SHADOW LIGHTS STAGE 2 - KEY For use in the intermediate element empty module Stage 2
Housing made of aluminium, painted matt black RAL 9005 The insert is fitted with 4 spots, painted black. The spots are fixed and not adjustable. Spot 1: 19°, inclination vertical -45°, angle horizontal +18° Spot 2: 19°, inclination vertical -45°, angle horizontal -18° Spot 3: 19°, inclination vertical -45°, angle horizontal 0° Spot 4: 19°, inclination vertical -35°, angle horizontal +36° Rated power 12W-24W With electronical ballast (220-240V 50/60Hz) Current rating 350 - 700mA Ingress protection IP65 (built-in) pre-wired

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6 W	CRI	80
Total flux	679 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	100%
		Total power	6 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6 W	CRI	80
Total flux	679 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	100%
		Total power	6 W

Light output 3 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6 W	CRI	80
Total flux	679 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	100%
		Total power	6 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6 W	CRI	80
Total flux	679 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	100%
		Total power	6 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 9.22 in

Width: 10.90 in

Height: 39.92 in

Adjustability

Fixed, Rotatable, Height adjustable

Design

Color of housing: Black

Electric

System power: 24 W

Protection

IP: 65