


Product data sheet

LED TRI PROOF LUMINAIRE 120CM WITH EMERGENCY LIGHT FUNCTION IP65 POWERSWITCH 25-40W, COLORSWITCH 3C 116026
ISOLED



LED diffuser light with emergency light function, IP65, Powerswitch, ColorSwitch, 120 cm, 25-40W | Dimensioned power: 40 W | Effective power: 40 W | Energy efficiency class: D (EU 2019/2015) | Nominal Voltage: 220 - 240 V AC | Protection class: 1 | Material: plastic | Surface color: white | Protection class: IP65 | Suitable for indoor use only | Allowable ambient Temperatures: -20° - 40° C | Beam angle: 120° fixed | Color temperature: 3000K - 5000K | Color rendering index: 84 (Ra 1-8) | Luminous flux: 5050 lm | Suitable for installation in furniture | Suitable for operating sites with fire hazard | Shock and impact resistant | Useful life: 50000 h (L80|B50) | Guarantee: 5 years | | FABRICATION: ISOLED 116026

Light output 1



1 x LED			
Nominal lamp power	40 W	LOR	100%
Lamp flux	5050 lm	ULOR	7%
Luminous efficacy	126 lm/W	Total flux	5050 lm
CCT	3000 K	Total power	40 W
CRI	84		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 47.24 in

Width: 3.74 in

Height: 2.95 in

Adjustability

Fixed

Design

Material impression: Plastic

Color of housing: White

Electric

System power: 40 W

Ballast: ECG

Integrated Switch: In housing

Suitable for feed-through wiring

Appliance Class: I

Protection

IP: 65

IK: 08

Designation labels: CE, F

Other operating numbers

Ambient temperature range: -4...104°F