

# Product data sheet


BARIS 40 LED UGR PLUS Z 4900LM I KL. IP44 1421MM 840 45W CZARNY 60D  
771217

LENA LIGHTING



771217 BARIS 40 LED UGR PLUS Z 4900lm I kl. IP44 1421mm 840 45W CZARNY 60D The BARIS 40 LED UGR PLUS luminaire was created to provide maximum comfort and work efficiency. With a UGR (Unified Glare Rating) value below 19, it minimizes the glare effect, affecting well-being, reducing fatigue and reducing the number of errors made. Suspended or surface-mounted lighting lamp with a very narrow cross-section. Its body is made of anodized aluminum profile in gray or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a lens with a parabolic louver.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	45 W	CRI	80
Total flux	4900 lm	LOR	100%
Luminous efficacy	109 lm/W	Total power	45 W

## Mounting mode

Pendant

## Shape and measurements

Length: 55.94 in

Width: 1.57 in

Height: 2.09 in

## Adjustability

Fixed

## Design

Material impression: Aluminum

Color of housing: Black

## Electric

System power: 45 W

Appliance Class: I

## Protection

IP: 44

IK: 03

Designation labels: CE