


Product data sheet

STREAMLINE PROJECTOR


S.1255H

SIMES



Version available on request without price surcharge. SPOTLIGHTS STREAMLINE PROJECTOR S.1255H module LED 2700K 220-240Vac ON-OFF Rated module luminous flux:: 7740lm Rated luminaire luminous flux: : 4973lm Rated module power: : 70.6W Rated luminaire power: : 74W Luminaire efficacy: : 67lm/W Voltage (AC): : 220-240Vac Frequency (AC): : 50/60Hz Voltage (DC): : 176-280Vdc Dimmable: : NOT DIMMABLE (ON-OFF) Electrical insulation class: : I Protection class IP: : IP65 Mechanical resistance: : IK07 CE SPECIAL VERSION ON REQUEST: this Luminaires can be supplied with a surcharge in class III (without power supply). Requires working remote power supply in constant current at 700mA $V_{fmin}=97.2Vdc$ $V_{fmax}=115.2Vdc$. LUMINAIRE TYPE Projector. IP rating IP 65 MATERIAL CHARACTERISTICS Die-cast EN AB-47100 aluminium housing with high corrosion resistance. Stone wash surface treatment prior to painting process. A4 grade Stainless Steel screws with 2,5-3% molybdenum content which increases the resistance against corrosion. Pre treated Silicone Gaskets. Painting Process : 3 Step Process 1) Surface treatment with BONDERITE. A heavy metal free chemical surface treatment containing ceramic nano particles giving a cohesive, inorganic and highly dense protective coating. 2) PRE POLYMERIZATION a process of introducing an epoxy primer with excellent characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content. 3) POLYMERIZATION a process with the application of polyester powder with high resistance against UV rays and harsh weather conditions. Resistance test protection for Marine applications for 1200h. Mechanical resistance IK 07 Maximum load capacity -- LIGHTING PERFORMANCE Clear toughened glass diffuser. LOR --. Compact electronic ballast to guarantee better lamp stability, lifetime and reduced energy consumption. The sophisticated optics focuses the beam and makes the light comfortable by reducing the direct glare of the light source. INSTALLATION AND MAINTENANCE Streamline projector suitable with the bracket that allows a 180° luminaire rotation. WIRING Supplied 1.5m cable section type H05RN-F sealed with B component epoxy resin, wired internally protected by silicon sheaths. Isolation: CLASS I . Available colours: Aluminium grey (cod.14), Anthracite grey (cod.24). Weight: 7.7811 Kg Glow Wire test: -- LED module included This luminaire contains built-in LED modules. In case of damage or malfunction please contact the manufacturer to receive additional instructions on how to replace and relative spare parts to order. The LED modules cannot be handled in the luminaire by the end user. This product contains a light source of energy efficiency class (EPREL - European Product Registry for Energy Labelling): F. LED modules are engineered accordingly to the existing regulations of Lumen Maintenance (LM80) and Technical Memorandum (TM21), where uniformity and quality of the light is 70,000 hours referred to L80 B10 Ta 25 ° C (50,000 hours referable to L80 B10 Ta 40°C). Lifespan of the luminaire min. 70.000 hours Ta 25°C, min. 50,000 hours at 40°C. Performance Ambient temperature Tq 25°C. Operating ambient temperature range is from -20°C to +50°C. Storage temperature range from -20°C to +60°C. ELECTRONIC EQUIPMENT SENSITIVE TO OVERVOLTAGE. We recommend installing surge protection devices "SPD" in the electrical system. Protection devices prevent the intensity of these phenomena's, protecting the appliances from the risk of being damaged and extending the lifespan. Outdoor luminaires are subject to all types of permanent, temporary, or transient electrical disturbances. Such disturbances can create permanent damage or failure affecting its performance and durability. The surge protection device (supplied by SIMES) is utilized to limit the destructive effect of these phenomena. We suggest that each luminaire must be connected to one protection device at not more than 10m away. For correct coordination of the protections, a surge protection device must also be provided inside the electrical panel of the system (the selection of this device must be carried out from the electrical designer and is not supplied by SIMES).

Light output 1 (integrated)



Lamp type		CCT	3000 K
Nominal lamp power	74 W	CRI	92
Total flux	4973 lm	LOR	100%
Luminous efficacy	67 lm/W	ULOR	100%
		Total power	74 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Length: 30.41 in

Width: 3.39 in

Height: 1.75 in

Adjustability

Tiltable

Design

Material impression: Aluminum, Glass

Color of housing: Silver gray

Designer: SIMES S.P.A.

Electric

System power: 74 W

Appliance Class: I

Protection

IP: 65

IK: 08

Designation labels: CE