Product data sheet


HALO SURFACE SILVER 1360MM
R48A136-9006C1940L1S
PLANLICHT



IP 20 CE


LED LO 4000K CRI>90 48,6W 4065lm https://katalog.planlicht.com/en-gb/fam-halo/

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.08 W	CRI	90
Total flux	508 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	6.08 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.08 W	CRI	90
Total flux	508 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	6.08 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.08 W	CRI	90
Total flux	508 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	6.08 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.08 W	CRI	90
Total flux	508 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	6.08 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.08 W	CRI	90
Total flux	508 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	6.08 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.08 W	CRI	90
Total flux	508 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	6.08 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.08 W	CRI	90
Total flux	508 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	6.08 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.08 W	CRI	90
Total flux	508 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	6.08 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 53.54 in
Width: 53.54 in
Height: 2.52 in

Adjustability

Fixed

Electric

System power: 48.6 W

Protection

IP: 20
Designation labels: CE