

Product data sheet

VOLKMAR III (WALL FITTING)


9.840.0082.00

LEIPZIGER LEUCHTEN



For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	125 W	LOR	55%
Lamp flux	6800 lm	ULOR	15%
Luminous efficacy	27 lm/W	Total flux	3714 lm
CCT	3400 K	Total power	137 W
CRI	54		

Mounting mode

Wall mounted

Shape and measurements

Height: 16.14 in

Diameter: 16.14 in

Design

Material impression: Matt, Plastic

Electric

System power: 137 W

Ballast: ECG

Protection

IP: 55

Designation labels: CE

Other operating numbers

Ambient temperature range: -4...77°F