
Product data sheet

CAELA RMS LED1100-840 OP WH WH APWH
60560002
ZUMTOBEL



LED wall and ceiling luminaire (round) with variable luminaire body for architectural structures (e.g. arches, waves); luminaire ultra-flat with integrated converter; modular LED luminaire concept; cover of polymethylmethacrylate (PMMA), opal with symmetric Lambertian light distribution; lamp(s): 1/15W LED1100-840; Colour rendering Ra > 80, colour temperature 4000 K (neutral white); Chromaticity tolerance (initial MacAdam): 3; Luminaire luminous flux: 1100 lm, Luminaire efficacy: 73 lm/W; service life: 50000 h for luminous flux at 80%; control gear: LED converter ; luminaire unit can be rotated through 355°and tilted through ±30°; luminaire consists of housing, cover and trim; housing of die-cast aluminium, white matt painted; trim in polycarbonate, white; Suspension consists of pre-assembled cable (2000 mm) and included white ceiling rose (pendant tube must be ordered separately); electrical connection: 5-pole connector terminal, through-wiring is not possible; total power: 15 W; mains voltage: 220-240V/ 50/60Hz; class of protection I; Dimensions: Ø334 x 74 mm; weight: 3 kg; Note: please order pendant tube separately. Can be cut to length on-site.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	15 W	CRI	80
Total flux	1100 lm	LOR	100%
Luminous efficacy	73 lm/W	Total power	15 W

Mounting mode

Pendant

Shape and measurements

Height: 2.91 in
Diameter: 13.15 in
Weight: 3 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 15 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 20
Designation labels: CE