
Product data sheet

SUPERLINEA SYSTEM 1536 DOWN LED 19.2W RA92 2700K 230V/50HZ IP20 SUPER WIDE FLOOD 75MA
723-72-DW-20-22-Y


EXENIA



IP 20

The new polyspherical or linear fly-eye optics have made it possible to conceive innovative lighting units with absolutely unique size/performance ratios. The Superlinea project aims to make system composition easy and intuitive by offering simple pre-assembled modules, with driver on board, to be connected in sequence with quick couplings and very few additional elements. The configurations offered are divided between: linear modular system in ceiling or suspension mode and simplified stand-alone, ceiling or suspension mode. We have prioritised longitudinal and transverse visual comfort in order to achieve consistently low UGR factors and efficiencies in the region of 140 lumens/W, while maintaining the slim, minimalist design typical of the Exenia style. Each suspended unit is available in single-emission and bi-emission modes

Light output 1



1 x LED

Nominal lamp power	21.5 W	LOR	100%
Lamp flux	2868 lm	ULOR	100%
Luminous efficacy	133 lm/W	Total flux	2868 lm
CCT	2700 K	Total power	21.5 W
CRI	92		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 0.94 in
Width: 60.63 in
Height: 3.35 in

Adjustability

Fixed

Electric

System power: 21.5 W

Protection

IP: 20