Product data sheet


HIGH_SYSTEM_LED_25W_4K_MICR_L574MM
905302_905141321_9055021_
PETRIDIS



IP 40

This luminaire combines the architectural style with the efficiency. It produces perfect lighting conditions without annoying reflections and that is why it can be used from entrance areas to offices. The visual benefit: The continuous-row system is illuminated absolutely uniformly from beginning to end, is economically efficient, is maintenance-free and it has long service life. Technical Features - Housing from aluminium profile, painted electrostatically in selected colour. - High efficient opal diffuser, microprismatic opal, anaglyph edition or blind aluminium cover painted. - Pure light without IR/UV radiation. - Efficient thermal management. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10). - Connection for operation on 230V/50Hz. Upon request: - Available with higher colour rendering index (CRI). - Available in IP54 protection version. - Connection for emergency lighting system, for one or three hours.

Light output 1



1 x LED

Nominal lamp power	25 W	LOR	63%
Lamp flux	4448 lm	Total flux	2786 lm
Luminous efficacy	178 lm/W	Total power	25 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 22.60 in
Width: 2.36 in
Height: 3.23 in

Adjustability

Fixed

Design

Material impression: Aluminum, Plastic

Electric

System power: 25 W
Controller: Dimmable 1..10V, DALI
Suitable for feed-through wiring
Appliance Class: I

Protection

IP: 40
Designation labels: CE