


Product data sheet

MIC 3 FLOODLIGHTS,PROJECTORS
MI-50381-W-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 200,000, 300,000 - Life time L80B10 Ta 50° 490,000, > 500,000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	28.8 W	CRI	80
Total flux	2926 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	28.8 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Height: 12.87 in
Diameter: 7.76 in
Weight: 3.7 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 28.8 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 07
Surface temperature: 40°C