




# Product data sheet

844 LED PANEL HE - UGR&ltltlt>/>19 - DIP SWITCH 3000K CRI 80 35W CLD WHITE  
150225-39  
DISANO



Housing: body in steel sheet and frame in aluminium. Diffuser: in high transmittance prismatic technopolymer. Internal PMMA slab. : UGR&ltltlt>/>19, according to standard EN 12464. Art 150211-00: not UGR&ltltlt>/>19 Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: Ceiling lighting fixture with external driver; it can be easily housed in false ceilings. Mounting: surface mounting on T-beams. Easy installation: quick connection without the need to open the luminaire, can be easily inserted into the ceiling. On request: - DIMM DALI CLD-D wiring (subcode -0041) - CLD-D (PUSH) (subcode -0045)

## Light output 1



1 x LED			
Nominal lamp power	35 W	LOR	100%
Lamp flux	4311 lm	Total flux	4311 lm
Luminous efficacy	123 lm/W	Total power	35 W
CCT	3000 K		
CRI	80		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 23.46 in  
Width: 23.46 in  
Height: 0.47 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 35 W  
Appliance Class: II

## Protection

IP: 43  
IK: 06  
Designation labels: CE