Product data sheet


162 LED DAMP-PROOF LIGHT FITTING
162 15L60 AUS H50 KE (16215 0364)
SCHUCH



IP 65 IK 05

LED damp-proof light fitting, 39 W, 6590 lm, 169 lm/W, Class I, IP65, symmetrical wide beam, 4000 K, CRI≥ 80, Ta -20 °C/+50 °C, L70>100000 h (@ Ta max), L80>70000 h (@ Ta max), L90>50000 h (@ Ta 25°C), Diffuser PMMA satined, Closure Stainless steel (1.4571), Housing Glass fibre reinforced polyester, Colour grey, for unprotected outdoor areas. Sturdy LED damp-proof light fitting for application in unprotected outdoor areas. Highly impact-resistant glass fibre reinforced polyester housing and frosted PMMA diffuser with high impact and UV resistance. Captive clips, multi-part, incl. two safety clips, silicone gasket and pressure compensation system. Powder-coated aluminium reflector with highly efficient Zhaga LED modules and ECG with overload and short circuit protection. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 1572,00 mm, Width/Diameter 197,00 mm, Height 125,00 mm, Net weight 4,87 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	39 W	CRI	80
Total flux	6590 lm	LOR	100%
Luminous efficacy	169 lm/W	ULOR	7%
		Total power	39 W

Mounting mode

Ceiling mounted, Pole top mounted, Wall mounted

Shape and measurements

Length: 61.89 in
Width: 7.76 in
Height: 4.92 in

Adjustability

Fixed

Electric

System power: 39 W
Appliance Class: I

Protection

IP: 65
IK: 05
Designation labels: CE