Product data sheet


DUOPRF 4X28W T16 HFI IP65
96549177
THORN LIGHTING



IP 65 IK 07

Ceiling recessed sealed luminaire for 4 x 28W T16 lamp(s). Electronic, DALI / DSI digital dimmable control gear. Body: Fabricated from sheet steel with white powder coated finish. Frame: steel with welded corners and finished in white powder coated. Gasket: silicone. Diffuser panel clear prismatic PET/G. IP65. Impact resistant and flame retardant (UK Building Regulations Part B2 classification TP[a]). Lamps to be ordered separately. Dimensions: 1192 x 590 x 90 mm Total power: 122 W Weight: 1.1 kg

Light output 1



4 x General service incandescent lamp

Nominal lamp power	28 W	LOR	63%
Lamp flux	10400 lm	Total flux	26208 lm
Luminous efficacy	215 lm/W	Total power	122 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 46.93 in
Width: 23.23 in
Height: 3.54 in
Weight: 1.1 kg

Electric

System power: 122 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: I

Protection

IP: 65
IK: 07
Designation labels: CE