
Product data sheet


P.THIRTY RECESSED L-SEG.HOR. SILVER OBD
P30-ELFH9006C1840V3G
PLANLICHT



IP 20 CE


LED VO 4000K 16,7W 2573lm DALI CRI90 https://katalog.planlicht.com/en-gb/search?q=p.thirty&type=1-profile-segment

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.39 W	CRI	90
Total flux	368 lm	LOR	100%
Luminous efficacy	154 lm/W	Total power	2.39 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.39 W	CRI	90
Total flux	368 lm	LOR	100%
Luminous efficacy	154 lm/W	Total power	2.39 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.39 W	CRI	90
Total flux	368 lm	LOR	100%
Luminous efficacy	154 lm/W	Total power	2.39 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.39 W	CRI	90
Total flux	368 lm	LOR	100%
Luminous efficacy	154 lm/W	Total power	2.39 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.39 W	CRI	90
Total flux	368 lm	LOR	100%
Luminous efficacy	154 lm/W	Total power	2.39 W

Light output 6 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.39 W	CRI	90
Total flux	368 lm	LOR	100%
Luminous efficacy	154 lm/W	Total power	2.39 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.39 W	CRI	90
Total flux	368 lm	LOR	100%
Luminous efficacy	154 lm/W	Total power	2.39 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 11.54 in

Width: 25.31 in

Height: 1.38 in

Electric

System power: 16.7 W

Protection

IP: 20

Designation labels: CE

Adjustability

Fixed