



Product data sheet

INFINITE PRO 854MM RECESSED OPTICELL
AK13-12X9CLDS14
LEDSC4



LedsC4 Infinite Pro 854mm Recessed Opticell AK13-12X9CLDS14V2 Lineal lighting system for indoor use. For downlighting. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Opticell. Warranty: 5 Years. Product net weight (Kg): 1.89 Product length (mm): 854 Product width or diameter (mm): 75 Product height (mm): 82 Ø of the hole for recessing (mm): 860x65 Permitted ceiling thickness: 0-25 Class 1. Luminaire not suitable for coating with insulation materials. IP: IN IP20 / OUT IP40. LED. No. of lampholders or LEDs: 1. LED brand: TRIDONIC. Driver brand: TCI. Maximum power of light source: 9.7W. Colour temperature: 4000K. Colour rendering index: 92. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 15.2. Photobiological risk: RG1. % de Flickering: <5%. Real flux (lm): 1718. Real lm/W: 153. Voltage / frequency range: 220-240/50-60Hz. Voltage: 120. Equipment included: Yes. Total power: 11.2. Power factor: 0.95. Dimmable equipment included: DALI-2/PUSH.

Light output 1



1 x LED			
Nominal lamp power	11.24 W	LOR	100%
Lamp flux	1718 lm	Total flux	1718 lm
Luminous efficacy	153 lm/W	Total power	11.24 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted, Standing / Bollard

Shape and measurements

Length: 2.05 in

Width: 44.72 in

Height: 3.54 in

Adjustability

Fixed

Electric

System power: 11.24 W

Appliance Class: I

Protection

IP: 40