



Product data sheet

603 DISANLENS UGR<LT/>19 4000K CRI 80 12W CLD WHITE
115520-19
DISANO



Housing: in pressed steel sheet, white ABS end caps. Diffuser: in polycarbonate with an outer micro-prismatic finish to control light distribution. : UGR<lt/>19, according to standard EN 12464. Coating: pre-painted in oven with polyester resin, UV-stabilised, phosphate pre-treatment. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: - with cable entry grommet and spacers for ceiling/wall mounting. - With vandal resistant closing mechanism. On request: emergency versions only for lengths of 1158/1440 mm.

Light output 1



| | | | |
|--------------------|----------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 12 W | LOR | 100% |
| Lamp flux | 1500 lm | ULOR | 4% |
| Luminous efficacy | 125 lm/W | Total flux | 1500 lm |
| CCT | 4000 K | Total power | 12 W |
| CRI | 80 | | |

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.39 in

Width: 6.10 in

Height: 2.32 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 12 W

Appliance Class: I

Protection

IP: 40

IK: 06

Designation labels: CE