


Product data sheet

ALBERTSLUND MINI LED UPGRADE KIT 3000K 14W CLO
91748-1001
LOUIS POULSEN



Albertslund Mini LED Upgrade Kit Design: Jens Møller-Jensen Concept: The fixture emits light directed downwards. The fixture emits symmetrical glare-free light directed downwards. The top shade helps direct the light downwards and prevent light from being emitted upwards. The white painted reflectors result in diffused and comfortable light distribution. The reflector ring protects against direct glare. The LED-upgrade kit (also referred to as LED Retrofit kit) allows you to replace the old electrical components, consol and lower reflector with a complete modern new unit, while retaining the original fixture. Finish: Aluminium coloured with textured surface, graphite with textured surface or grey, powder coated. Materials: Heat sink/fixture housing: Die-cast aluminium. Console: Die-cast aluminium. Struts: Stainless steel. Mounting LED Upgrade kit available for upgrading Albertslund with CFL light sources produced from 2005 and onwards. Installation cable: 4m, 3x1.5mm² (Class I) or 4m, 2x1.5mm² (Class II). Looping: Approved. Delivered with outdoor LED driver with transient protection. LED driver in fixture head. Cable to be mounted in fuse box (not included). Class Ingress protection IP66. Electric shock protection I w. ground, II w/o ground. IK10. Sizes and weights: Width x Height x Length (mm) 660 x 565 x 660 Max 4.8 kg Information: LED Upgrade kit available for upgrading Albertslund with CFL light sources produced from 2005 and onwards. Dimming options available: DALI, CLO, and night time dimming (default setting: 50% power in 8 hours).

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	14 W	CRI	80
Total flux	1213 lm	LOR	69%
Luminous efficacy	87 lm/W	Total power	14 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 22.44 in

Diameter: 25.98 in

Adjustability

Fixed

Electric

System power: 14 W

Appliance Class: II

Protection

IP: 66

IK: 10