

Product data sheet

LED ECO STREET L 70W 865 WV
4058075279056
LEDVANCE




IP
66

IK
08

LED ECO Streetlight is a reliable LED street light for residential applications. The range consists three housing sizes for different wattages, with dust-free and cost effective design. The range has two levels of system efficacy, 100lm/W and 120lm/W, for different needs. Its high grade aluminum housing ensures reliable operation, high quality PC lens provides effective lighting distribution. This street light range is ideal for residential lighting purpose.Slim, aesthetical housing combined with dust-free design. Available in 30w/50w/70W for 100lm/w range, and 30W/45W/60W for 120lm/W range. Easy connection by providing pre-wired 0.5m cable. Precise lens design provides uniform and less glare lighting. High grade aluminum housing ensures reliable operation. Surge protection rated up to 10 KV (L-N), with replaceable SPD. Lifetime 50000 hours. IP66, IK08. CB, RoHS available.

Light output 1



1 x LED			
Nominal lamp power	70 W	LOR	109%
Lamp flux	7000 lm	Total flux	7615 lm
Luminous efficacy	100 lm/W	Total power	70 W
CCT	6800 K		
CRI	80		

Mounting mode

Pole top mounted

Electric

System power: 70 W

Shape and measurements

Length: 7.87 in
Width: 3.94 in
Height: 0.39 in

Protection

IP: 66
IK: 08

Adjustability

Fixed