

Product data sheet


E04 CEILING ANTHRACITE
E04026
LUCEPLAN



IP
20


Apparecchi a soffitto in due diametri (70 mm e 134 mm) e differenti lunghezze. L'elemento di chiusura, realizzato in alluminio lucidato, in contrasto con la finitura esterna del corpo, conferisce all'oggetto leggerezza evidenziando il dettaglio del sistema di chiusura a filo. La posizione arretrata della sorgente aumenta l'angolo di schermatura e il comfort luminoso.

Light output 1




1 x Metal halide lamp

Nominal lamp power	70 W	Socket	G12
Lamp flux	6600 lm	LOR	61%
Luminous efficacy	54 lm/W	Total flux	4048 lm
CCT	4000 K	Total power	75 W
CRI	84		



1 x Metal halide lamp

Nominal lamp power	70 W	Socket	G12
Lamp flux	6600 lm	LOR	61%
Luminous efficacy	54 lm/W	Total flux	4048 lm
CCT	3000 K	Total power	75 W
CRI	84		



1 x Compact fluorescent lamp

Nominal lamp power	18 W	Socket	Gx24Q-2
Lamp flux	1200 lm	LOR	61%
Luminous efficacy	10 lm/W	Total flux	736 lm
CCT	3000 K	Total power	75 W
CRI	85		

Mounting mode

Ceiling mounted

Electric

System power: 75 W

Shape and measurements

Length: 5.27 in

Width: 5.27 in

Height: 14.65 in

Adjustability

Fixed

Protection

IP: 20