


Product data sheet


LED SURFACE MOUNTED/HANGING LIGHT LINEAR GRID 20W, STACKABLE, WHITE, COLORSWITCH 3000|3500|4000K 114060

ISOLED



LED surface-mounted/pendant light Linear louvre 20W, bayable, white, ColorSwitch 3000|3500|4000K | Dimensioned wattage: 20 W | Effective wattage: 20 W | Energy efficiency class: E (EU 2019/2015) | Nominal Voltage: 220 - 240 V AC | Material: PC/aluminum | Surface color: white | Protection class: IP20 | Suitable for indoor use only | Allowable ambient Temperatures: -20° - 40° C | Beam angle: 100° fixed | Color temperature: 3000K - 4000K | Color rendering index: 85 (Ra 1-8) | Luminous flux: 2000 lm | Usable life: 70000 h (L80|B50) | Warranty: 2 years | FABRICATION: ISOLED 114060

Light output 1



1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2000 lm	Total flux	2000 lm
Luminous efficacy	100 lm/W	Total power	20 W
CCT	3000 K		
CRI	85		

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 23.78 in

Width: 2.36 in

Height: 2.76 in

Adjustability

Height adjustable

Design

Material impression: Aluminum, Plastic

Color of housing: White

Electric

System power: 20 W

Ballast: ECG

Integrated Switch: In housing

Protection

IP: 20

Designation labels: CE

Other operating numbers

Ambient temperature range: -4...104°F