Product data sheet

SENSE AIR WHITE 36W LED 4000K RA>80 5046212242

SG ARMATUREN







Energy efficient LED panel with a slimline profile that looks modern as it floats in the room. The fixture is produced in a matt white powder-coated aluminium. The prismatic diffuser provides a glare-free light, and it offers both indirect and direct lighting. Ideal for offices and meeting rooms. The ceiling bracket can be fitted externally using concealed or visible cabling. It can also easily be added to an ordinary 60x60 ceiling panel. Connection using quick release terminals for easy forwarding is possible. Low voltage power runs through the wires of the ceiling bracket ensuring it is a highly elegant solution without unsightly power cables in the way. Supplied as DALI or non-dimmable. Dip switches on the driver makes it possible to adjust down the lighting level if desired. Emergency lighting version also available. Light distribution:

Direct/Indirect Light technic LED (not exchangeable) 36W 4000K Ra>80 SDCM 3 L80/B20 >50.000 hrs at Ta=25°C Control/Dimming On/Off

Protection Class I IP20 Energy and approvals A++ CE Materials and finish Housing: Steel, Aluminium Colour: White Optics: PMMA

Polymethylmethacrylat Mounting/Connection Suspended, Indoor 2x2m wire kit Screwless terminal block Max. luminaires per circuit breaker:

B10: 14, B16: 23, C10: 22, C16: 36

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	36 W	CRI	80
Total flux	3600 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	25%
		Total power	36 W

Mounting mode

Pendant

Shape and measurements

Length: 47.24 in Width: 8.27 in Height: 0.59 in

Adjustability

Height adjustable

Electric

System power: 36 W Appliance Class: I

Protection

IP: 20