
Product data sheet


NADELSPOT MINI
581598.0031.2
RZB



IP 65 IK 06

Series: Nadelspot Type of Protection: IP 65 Protection Class: I Voltage: 220 - 240 V / 50 Hz Housing: die cast aluminium, powder coated. Light emission: transparent glass, flush at the top. Screws: stainless steel. LED with integrated converter, for 3x1.5mm² cables, max diameter 10mm. LED included. Available Colours: anthracite metallic Type of Installation: Wall (surface) Dimensions: L 112, B 96, H 96 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK06 (1 Joule) Luminaire flux LED: 280lm System power: 7,2W Beam Angle: 35°/44°/43°/43° Unified Glare Ratio: 9,7 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	7.2 W	CRI	80
Total flux	280 lm	LOR	100%
Luminous efficacy	39 lm/W	ULOR	50%
		Total power	7.2 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.78 in
Width: 4.41 in
Height: 3.78 in

Adjustability

Fixed

Electric

System power: 7.2 W

Protection

IP: 65
IK: 06