


Product data sheet

LBX 6 BOLLARDS
LB-10842-W40
LIGMAN



- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° > 55,400 - Life time L80B10 Ta 50° > 55,400 - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	21 W	CRI	80
Total flux	900 lm	LOR	100%
Luminous efficacy	43 lm/W	ULOR	19%
		Total power	21 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 4.92 in

Width: 4.92 in

Height: 31.50 in

Weight: 8.5 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 21 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65

IK: 09

Surface temperature: 40°C