


Product data sheet

ORBIT PLUG&PLAY SMALL HOLE COVER
25-E022-DL-EH
LEDSC4




LedsC4 Orbit Plug&Play Small Hole Cover 25-E022-DL-EH Floor lamp for outdoor use. Metres of cable included: 3. Structure material: Aluminium. Structure finish: Gold. Diffuser material: Polycarbonate. Diffuser finish: OPAL. UV protection. Warranty: 5 Years. Product net weight (Kg): 0 Product width or diameter (mm): 350 Product height (mm): 1805 Class 1. IP: IP66. IK: IK10. LED. No. of lampholders or LEDs: 1. LED brand: OSRAM. Maximum power of light source: 9.8W. Colour temperature: SW 2700-3200-4000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 19.7. Photobiological risk: RG1. Real flux (lm): 764. Real lm/W: 66. Voltage / frequency range: 100-240/50-60Hz. Voltage: 3. LED brand: OSRAM. Colour temperature: SW 2700-3200-4000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 19.7. Photobiological risk: RG1. Real flux (lm): 764. Real lm/W: 66. Voltage: 3. Equipment included: Yes. Total power: 11.5. Power factor: 0.95. Dimmable equipment included: ON-OFF.


Light output 1



1 x LED			
Nominal lamp power	11.5 W	LOR	100%
Lamp flux	758 lm	Total flux	758 lm
Luminous efficacy	66 lm/W	Total power	11.5 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	11.5 W	LOR	100%
Lamp flux	764 lm	Total flux	764 lm
Luminous efficacy	66 lm/W	Total power	11.5 W
CCT	3200 K		
CRI	80		



1 x LED			
Nominal lamp power	11.5 W	LOR	100%
Lamp flux	699 lm	Total flux	699 lm
Luminous efficacy	61 lm/W	Total power	11.5 W
CCT	2700 K		
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 9.84 in

Width: 9.84 in

Height: 72.83 in

Adjustability

Fixed

Electric

System power: 11.5 W

Appliance Class: I

Protection

IP: 66

IK: 10