
Product data sheet

BASIC DÉCO XXL SUSPENDED - G4
BG4ASE-830M-D900-UW
LIGHTNET



LED pendant luminaire. Direct-indirect or direct-only light distribution. Luminaire body made of aluminium profile with overall height of 100mm. Outer housing and Décorative reflector ring available in various finishes and combinations, e.g. white, silver, graphite, black, gold or copper coated. For surface options and combinations check Lightnet Surface Collection or Bi-Colour Selection. Recessed microprismatic screen with optimized glare reduction especially for workplaces. Opal diffuser made of acrylic glass. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	106 W	CRI	82
Total flux	10743 lm	LOR	100%
Luminous efficacy	101 lm/W	Total power	106 W

Mounting mode

Pendant

Shape and measurements

Height: 35.43 in
Diameter: 35.43 in

Adjustability

Height adjustable

Electric

System power: 106 W

Protection