

# Product data sheet

LED MINI PANEL RPE SERIES 6W 3000/4000/6500K

RPE-6/3C


MPE



IP  
20

- Round shape - Recessed - mounted on ceiling or use additional SRPE accessories for floating mounting - Light guide plate made of PMMA plastic for uniform light distribution - Driver is integrated inside the light. - The light has 3 color modes: Warm White-Cool White-Natural - Size: Ø150 x 25 mm - Cut out: Ø133mm - Voltage: 110-265VAC - Power: 6W - Power Factor (PF): >0.5 - Luminance: 500 lm - Color Temperature (CCT):2800-3200K/ 6000-6500K/4000-4500K - RA >80 High Color Rendering Index - Beam angle: 120° - Chip LED: SMD 2835 - Life Time: 30,000 hours - Instant Light: 0s - European Standard CE - RoHS

## Light output 1



### 1 x LED Module

Nominal lamp power	6 W	LOR	100%
Lamp flux	1500 lm	Total flux	1500 lm
Luminous efficacy	245 lm/W	Total power	6.11 W
CCT			
CRI	82		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 7.24 in

Width: 5.91 in

Height: 1.54 in

## Adjustability

Fixed

## Electric

System power: 6.11 W

## Protection

IP: 20