

Product data sheet


TRIONA PRISMATIK
312298.004.1
RZB



IP
20

Series: Triona Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Deckenbaldachin (D 260 mm, H 40 mm) Aluminium eloxiert. Mit Verbindungsleitung zwischen Leuchte und Deckenbaldachin. Mit 3-Punkt-Stahlseilabhngung, stufenlos hhenverstellbar. Leuchtenrahmen Metall pulverbeschichtet. Diffusorsegmente (Lichtaustritt indirekt) aus vergilbungsfreiem Kunststoff (PMMA) opal. Diffusor (Lichtaustritt direkt) aus Kunststoff (PMMA) opal / mikroprismatisch. Betriebsgert eingebaut. Leuchtmittel (LED) im Lieferumfang enthalten. Available Colours: silver, metallic Type of Installation: Pendant Dimensions: D 681, H 52 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Luminaire flux LED: 6550lm System power: 68W Beam Angle: 95° Number of fittings B10A: 6 Number of fittings B16A: 10 Inrush current: 40A Unified Glare Ratio: 17,5 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	68.3 W	CRI	80
Total flux	6550 lm	LOR	100%
Luminous efficacy	96 lm/W	ULOR	27%
		Total power	68.3 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 2.05 in
Diameter: 26.81 in

Adjustability

Fixed

Electric

System power: 68.3 W

Protection

IP: 20