


# Product data sheet

DIAMO MD 700-927 SWI SP-DWH WH  
60210953  
ZUMTOBEL



Miniaturised LED light module for precise accent lighting; compact construction and purist appearance; precise light distribution without stray light, with very good glare control; maximum brilliance due to specially designed reflector; lamp(s): 1/12W LED700-927; (15 °) SPOT distribution characteristic; reflector: black with white deco edge; Colour rendering Ra > 90, colour temperature 2700 K (warm white); Chromaticity tolerance (initial MacAdam): 3; Luminaire luminous flux: 700 lm, Luminaire efficacy: 58 lm/W; service life: 50000h at 80% luminous flux; with control unit, switchable luminaire; as multifunctional lamp unit rotatable (180°) and tiltable (2x20°) in combination with DIAMO Gimbal installation frame with trim or plaster surround (trimless), or fixed and rigid for increased visual comfort in combination with DIAMO Deep Source installation frame/ring; innovative thermal design achieves passive cooling; housing made of die-cast aluminium, white; reflector: polycarbonate, black; luminaire wired with halogen-free leads; power connection: 2-pole terminal; total power: 12 W; mains voltage: 220-240V/ 0/50/60Hz ; simple, tool-free mounting of modules in installation frame (Gimbal / Deep Source) via CLIX technology; Dimensions: Ø65 x 89 mm, weight: 0.35 kg; Note: Various colour combinations (design personalisations) of single components possible due to modular construction, and orderable as variant via myDIAMO: Note: The DIAMO Gimbal installation frame (single, double or triple) and DIAMO Deep Source installation frame/ring must be ordered separately.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	12 W	CRI	90
Total flux	700 lm	LOR	100%
Luminous efficacy	58 lm/W	Total power	12 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 3.50 in  
Diameter: 2.56 in  
Weight: 0.347 kg

## Design

Material impression: Aluminum  
Color of housing: White

## Electric

System power: 12 W  
Voltage: 220-240 V AC  
Appliance Class: II

## Protection

IP: 20  
Designation labels: CE