


Product data sheet

JUNISTAR SOFT BLACK 760LM 3000K RA 98 TRAILING EDGE DIMMING
7021989033134
SG ARMATUREN



Attractive exclusive downlight for indoor or outdoor use, particularly well suited to basic lighting due to its very low unified glare rating. Well integrated LED chip and associated dimmable driver. Made of die-cast powder-coated aluminium, glass diffuser. 42° beam angle angle. Low recessed downlight with hole size Ø83mm. Light distribution Direct Light technic LED (not exchangeable) 11W 3000K Ra 98 SDCM 2 L90/B10 >100,000 hrs Control/Dimming Trailing edge dimming Protection Class II SELV IP54 Materials and finish Housing: Aluminium Colour: Black (RAL 9004) Optics: Tempered glass Mounting/Connection Recessed, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 77, B16: 123, C10: 77, C16: 123

Light output 1



1 x LED			
Nominal lamp power	11 W	LOR	100%
Lamp flux	760 lm	Total flux	760 lm
Luminous efficacy	69 lm/W	Total power	11 W
CCT	3000 K		
CRI	98		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.70 in
Width: 3.70 in
Height: 2.09 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 11 W
Appliance Class: II

Protection

IP: 54