




Product data sheet

SINTESI SYSTEM - CEILING FIXTURE - WITH UGR<LT/>19 SCREEN 3000K CRI 80 56W CLD-D-D WHITE
22010111-3941
DISANO



Housing: in extruded 6060 aluminium alloy. Removable extruded aluminium 6060 alloy top cover to allow electrical line connection. Injection-moulded ABS V0 end caps. Diffuser: in transparent PMMA with UGR<lt/>19 shielded micro-lenticular film. : UGR<lt/>19, according to standard EN 12464. Coating: epoxy polyester powder coating resistant to UV rays. LED: 80%: 50000h (L80B20) Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529.

Light output 1



| | | | |
|--------------------|---------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 56 W | LOR | 100% |
| Lamp flux | 4737 lm | Total flux | 4737 lm |
| Luminous efficacy | 85 lm/W | Total power | 56 W |
| CCT | 3000 K | | |
| CRI | 80 | | |

Mounting mode

Ceiling mounted

Shape and measurements

Length: 91.02 in

Width: 2.76 in

Height: 3.50 in

Adjustability

Fixed

Design

Material impression: Aluminum

Color of housing: White

Electric

System power: 56 W

Appliance Class: I

Protection

IP: 40

IK: 07

Designation labels: CE