
Product data sheet

MATRIX Q10 DARK C - DIP SWITCH - UNIVERSAL ADAPTER 4000K CRI 90 20W CLD WHITE
22103611-00


DISANO



IP 40 IK 07

Housing: in die-cast aluminium. front in black polycarbonate (available in white uopn request). Optics: high-efficiency PMMA lens with a very low glare coefficient. Coating: epoxy polyester powder coating resistant to UV rays. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: universal adapter. Warnings: DALI dimmer version -1241 to be used with OMNITRACK PLUS. On request: - version with CASAMBI (MAX 40W).

Light output 1



1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	1873 lm	Total flux	1873 lm
Luminous efficacy	94 lm/W	Total power	20 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 5.39 in
Width: 2.52 in
Height: 1.42 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 20 W
Appliance Class: II

Protection

IP: 40
IK: 07
Designation labels: CE