

Product data sheet

DECORATIVE LIGHTING

V1-R0-0G524-30000-2007830 ENSO G 1100X980X40 SUSPENDED 78W 3000K

VARTON




IP
20

IK
06

Input voltage (AC, 50Hz), V: 198...264 AC frequency, Hz: 50 Flicker, %: 5 Climatic modification and category of placement: YXЛ4 Protection class: I Housing material: Aluminium Mounting method: Pendant Ingress protection (IP): IP20 Impact resistance: IK06 Power factor: 0,95 https://www.varton.ru/products/interernoie-dekorativnoie-osveshchenie/enso-g/enso-g-1100kh980kh40-podvesnye/svetilnik-var-ton-enso-g-1100kh980kh40-mm-78-vt-cri90-3000-k-podvesnoy-ral9003-belyy-matovyy-s-rassei_1/

Light output 1



1 x LED			
Nominal lamp power	78 W	LOR	100%
Lamp flux	5900 lm	Total flux	5901 lm
Luminous efficacy	76 lm/W	Total power	78 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant

Shape and measurements

Length: 43.31 in

Width: 38.58 in

Height: 1.57 in

Adjustability

Fixed

Electric

System power: 78 W

Protection

IP: 20

IK: 06