

Product data sheet

ALFONS I FF LED (ASYMMETRICAL)

9.136.8215.04-3


LEIPZIGER LEUCHTEN



IP
66

recom. pole height: 4.00m – 7.00m light standards: low and medium lighting requirements lamp: incl. 1 or 2 FF IV-X LED module(s), easy to replace colour temperature: 4.000K neutral white or 3.000K warm white LED gear: electronic driver, up to 100.000 hours; driver with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire lifetime LED life expectancy: up to 100.000 hours, 50.000 hours/ L100 for minimum maintenance costs due to an excellent thermal management light control: at extra cost: power reduction, dimming or CLEVER LIGHT optical system: directed light (multi layer) provided by an exchangeable, anti-aging lens technology light distribution: asymmetrical luminaire head: die cast aluminium, powder coated colour: DB 703; other colours on request glazing: flat, clear toughened glass glazing wiring: completely wired; via a plug and socket connector within the luminaire head; luminaire head to be hinged upward installation: for top or side entry; ASA 60 or ASA 76 to be ordered separately: • ASA 60 for side entry \varnothing 48mm up to 60mm (0°, -5°, -10°, -15°) or for top entry \varnothing 60mm (0°, 5°, 10°, 15°) • ASA 76 for top entry \varnothing 76mm (0°, 5°, 10°) accessory: adapter ASA, column, pole accessories, wall bracket, cable – to be ordered separately application areas: parks, boulevards, schools, home for elderly people, hotels, factory premises, residential and local distribution roads, main streets, car parks, pedestrian and cycle lanes, holiday parks

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	30 W	CRI	70
Total flux	3759 lm	LOR	100%
Luminous efficacy	125 lm/W	Total power	30 W

Mounting mode

Pole integrated, Pole top mounted

Shape and measurements

Length: 21.65 in
Width: 9.41 in
Height: 7.24 in
Weight: 6.8 kg

Adjustability

Height adjustable

Electric

System power: 30 W

Protection

IP: 66