Product data sheet


KSC418SC-TT
KSC418SC-TT
RP-TECHNIK



IP 54 IK 03

Innovative plastic emergency exit sign and safety luminaire for universal mounting. Suited to inscription on one or two sides, as well as illumination of firefighting and first aid stations, with the 5 lux rating required as a minimum according to EN 1838. Thanks to the snap-in mechanism between the upper and lower part, the luminaire has a harmonious look and appears closed all the way round. The luminaire is connected to the mains in the ceiling section. When closed, the luminaire is powered via contact plugs. This greatly simplifies mounting and makes convenient connection possible despite the small size of the luminaire.

Light output 1 (emergency)



1 x LED

Nominal lamp power	3.9 W	LOR	89%
Lamp flux	85 lm	Total flux	76 lm
Luminous efficacy	22 lm/W	Total power	5.3 W
CCT	6500 K		
CRI	75		

Mounting mode

Ceiling mounted, Wall recessed

Shape and measurements

Length: 1.34 in
Width: 9.84 in
Height: 6.85 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 5.3 W
Appliance Class: I

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Protection

IP: 54
IK: 03
Designation labels: CE

Other operating numbers

Ambient temperature range: 5...104°F