



Product data sheet

UNI-BRIGHT DRUM 3PH 10-20W - WW - BLACK - 55DEG
DR3F102230B + DRLE551022
PROLED (MBN GMBH)




Tracklight for standard 3-phase track. Universal global 3-phase adapter included. Driver included. Not dimmable.


Light output 1




1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	1960 lm	Total flux	1960 lm
Luminous efficacy	98 lm/W	Total power	20 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	18 W	LOR	100%
Lamp flux	1770 lm	Total flux	1770 lm
Luminous efficacy	98 lm/W	Total power	18 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	14 W	LOR	100%
Lamp flux	1370 lm	Total flux	1370 lm
Luminous efficacy	98 lm/W	Total power	14 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

10 W
980 lm
98 lm/W
3000 K
90

LOR
Total flux
Total power

100%
980 lm
10 W

Mounting mode

Ceiling mounted, Contact rail, Contact rail

Shape and measurements

Length: 6.38 in
Width: 2.56 in
Height: 8.54 in
Weight: 0.68 kg

Adjustability

Rotatable, Tilttable

Electric

System power: 10-20 W
Appliance Class: II

Protection

IP: 20

Other operating numbers

Ambient temperature range: 14...113°F