Product data sheet


DEFINE LED WALL MOUNT LUMINAIRE S122RDIW-S865D710U840-4F0-1E-UDD-F COOPER LIGHTING



Wall Mount Slot family in 2", 3", 4" and 5" housing sizes, Specifiable to the nearest 1', Multiple lensing options: flush satin, drop, regressed and asymmetric, Multiple lumen packages, 0-10V dimming standard; DALI dimming available, 2700K, 3000K, 3500K, 4000K & 5000K correlated color temperatures, VividTune CCT tuning options from 3000K–5000K or 2700K-6500K, Integral Wavelinx and Stand-alone sensors available, Customizable in-wall, in-ceiling and wall-to-ceiling corners available, DLC listed configurations available

IP 47

Light output 1 (integrated)



| Lamp type | LED | CCT | 4000 K |
|--------------------|----------|-------------|--------|
| Nominal lamp power | 53.6 W | CRI | 80 |
| Total flux | 5911 lm | LOR | 100% |
| Luminous efficacy | 110 lm/W | ULOR | 48% |
| | | Total power | 53.6 W |

Wall mounted

Shape and measurements

Length: 48.00 in Width: 2.00 in Height: 0.39 in

Adjustability

Fixed

Electric

System power: 53.6 W

Protection

IP: 47