
Product data sheet

RINGO STAR 60MM ACOUSTIC SUSPENDED - G3
RG3ASE-830H-D2000-U-AY
LIGHTNET




LED acoustic pendant luminaire. Direct-indirect or direct-only light distribution. Luminaire body made of aluminium profile with 60mm track width. 5 different diameters from 600mm to 2000mm. Surface silver, white, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Acoustic element in 4 options (Green Moss, Yellow Felt, Graphite Felt or White Perforated). Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90.

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	17 W	CRI	82
Total flux	1426 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	17 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	17 W	CRI	82
Total flux	1426 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	17 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	17 W	CRI	82
Total flux	1426 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	17 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	17 W	CRI	82
Total flux	1426 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	17 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	17 W	CRI	82
Total flux	1426 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	17 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	17 W	CRI	82
Total flux	1426 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	17 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	17 W	CRI	82
Total flux	1426 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	17 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	17 W	CRI	82
Total flux	1426 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	17 W

Mounting mode

Pendant

Shape and measurements

Length: 30.12 in
Width: 2.36 in
Height: 3.15 in

Adjustability

Height adjustable

Electric

System power: 136 W

Protection