Product data sheet

HUMID LED 6000 840 NÖD
453505-NÖD
NOKALUX




NOKALUX

IP 44

D-märkt kapslad allroundarmatur IP 44. Slimmad stomme av galvaniserat stål, vitlackerat RAL 9016. Gavlar av slagtålig plast. Kupa av opal linjeprismatisk akryl. Flexibelt montage dikt tak, på vägg- konsol, armaturskena eller lina. Anslutning via gavel eller ovansida. Som standard överkopplingsbar 5-polig plint. Sensor tänder och släcker vid rörelse. Sensor TDC tänder vid rörelse för att sedan gå ner till 10%, släcker vid frånvaro efter 30 min. Finns i ett flertal utförande beträffande styrning, montage och anslutning. Livslängd: L80 Ta25 70000h (B50) Humid LED 8500 har 65000h MacAdam 3 SDCM CRI: >80 Klass: IP 44 D I CE

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	50.31 W	CRI	83
Total flux	6061 lm	LOR	100%
Luminous efficacy	120 lm/W	ULOR	9%
		Total power	50.31 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 6.10 in
Width: 58.66 in
Height: 1.97 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 50.31 W
Appliance Class: I

Protection

IP: 44