


Product data sheet

TRIONA PRISMATIK
312297.002.76
RZB




IP
20

IK
03

Series: Triona Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Halterung und Leuchtenrahmen Metall pulverbeschichtet. Diffusorsegmente (Lichtaustritt indirekt) aus vergilbungsfreiem Kunststoff (PMMA) opal. Diffusor (Lichtaustritt direkt) aus Kunststoff (PMMA) opal / mikrop Prismatisch. Betriebsgerät eingebaut. Leuchtmittel (LED) im Lieferumfang enthalten. Available Colours: white
Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 681, H 88 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 6300lm System power: 68W Beam Angle: 95° Number of fittings B10A: 6 Number of fittings B16A: 10 Inrush current: 40A Unified Glare Ratio: 17,2 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	68.3 W	CRI	80
Total flux	6300 lm	LOR	100%
Luminous efficacy	92 lm/W	ULOR	27%
		Total power	68.3 W

Mounting mode

Wall mounted

Shape and measurements

Height: 2.05 in
Diameter: 26.81 in

Adjustability

Fixed

Electric

System power: 68.3 W

Protection

IP: 20
IK: 03